



FA 30 600 10

FA 30 600 15



FA 30 600 13



HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N° 2777/10964-01/E06-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 600 13	FA 30 600 10	FA 30 600 15
LG. 	1.3 m	1 m (connectors included)	1.5 m (connectors included)

	Max. 100 KG		
CE	EN 355:2002		
MAT.	 PA 11 mm Polyamide		
	45 mm		
	---		
	NO		
+	VG 11.063		
	0.74 KG	1.60 KG	1.82 KG



Largeur de l'absorbeur d'énergie

Width of the energy absorber

Ancho del absorbedor de energía

Larghezza del assorbitore di energia

Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur

Length Max. user weight

Longitud Peso máximo del usuario

Lunghezza Peso Max. dell'utente

Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas

Material of top connector / bottom connector

Material conector alto / conector bajo

Materiale connettore alto / connettore basso

Material oberes / unteres Verbindungselement



Ouverture

Gate opening

Apertura

Apertura

Öffnung



Homologué pour le travail à proximité d'arêtes vives

Approved for work near sharp edges

Homologado para trabajo cerca de aristas vivas

Omologato per lavoro in prossimità di spigoli vivi

Zugelassen für Arbeiten in der Nähe scharfer Kanten